

**Pneumatic Tool Lubrication-General Guidelines-Florida Pneumatic**

Mechanism	Oil-Grease type	Oil-Grease volume	Brand part # ref	Other Brand part # ref
DynaPact-Twin Clutch	SAE 30	20cc at service interval	Any SAE 30 weight	
Oil lubricated twin hammer	SAE 40	20cc at service interval	Any SAE 40 weight	
Grease lubricated Twin/Pin-less/Jumbo hammer	Lithium Compounded Complex Grease	10 cc at service interval	E.T. Lubricants #4092 LLGI # 2	Lubricate # 1424
Air motors	SAE 5 or SAE 10	1 cc daily-if there is no built-in lubricator	Air tool oil or any SAE 5 or 10 weight machine oil	
Grinder gears	Synthetic High Temp Grease	4cc 48 hrs continuous running	E.T. Lubricants # 4501 NLG1 # 2	Shell S2V220 2 or Lubricate SVO-255
Drill/Driver gears	Synthetic High Temp Grease	2cc 48 hrs continuous running	E.T. Lubricants # 4501 NLG1 # 2	Shell S2V220 2 or Lubricate SVO-255
Bearings all Tools	Lithium Multi Purpose Grease	At service interval	E.T. Lubricants # 4081 NLG1 # 2	Shell S2V220 2 or Lubricate SVO-222
VIBROTHERM DRIVE® 1058-VXL VIBROTHERM DRIVE® 1059-VXL	Chevron Moly Grease EP	30cc at service interval	Chevron #255659, 255660	
VIBROTHERM DRIVE® 1178-VXL	Chevron Moly Grease EP	45cc at service interval	Chevron #255659, 255660	
VIBROTHERM DRIVE® 1778-VXL	Chevron Moly Grease EP	70cc at service interval	Chevron #255659, 255660	



Universal Tool



FLORIDA  
 PNEUMATIC