



# 6700-6G

## GEARED PLANETARY MOTION SANDER

### FEATURES

- Lubrication free air motor
- Patented double sealed motor prevents dust contamination
- Low vibration level 2.5m/sec<sup>2</sup>
- Advanced silencing technology reduces noise level to 78 d(B)A
- Low average air consumption of 3.0 CFM
- Ergonomic throttle lever design increases comfort

### SPECIFICATIONS

|                                       |             |
|---------------------------------------|-------------|
| Pad/Bonnet Size (in.)                 | 6           |
| Orbit (in)                            | 3/16        |
| Pad Type                              | Hook & Loop |
| No. Vacuum Pad Holes                  | 0           |
| Free Speed (RPM)                      | 900         |
| Weight (lbs.)                         | 3.4         |
| Length w/ Pad Fitted (in.)            | 10.2        |
| Width w/ Pad Fitted (in.)             | 6.0         |
| Height w/ Pad Fitted (in.)            | 4.5         |
| Noise Level d(B)A                     | 78          |
| Vibration Level (m/sec <sup>2</sup> ) | 2.5         |
| Air Cons. (CFM)                       | 3.0         |
| Air Inlet (in.) NPT/BSP               | 1/4         |



Styled for perfection and built to last!

# AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation  
851 Jupiter Park Lane / Jupiter, Florida 33458

[www.AIRCAT.com](http://www.AIRCAT.com)

(800) 356-3392