

AIRCAT

PNEUMATIC TOOLS

1058-VXL

Compact Impact Wrench

FEATURE

- Provides 750 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the characteristic aircat unmatched low noise levels;
- The patented grip design provides the operator the ultimate comfort.
- Investment into tooling and materials and a triple injection molding processes enable aircat to produce cosmetic designs that are unmatched in the industry.
- "three year warranty".

SPECIFICATIONS

Maximum torque (Nm): 750
Square drive (in.): 1/2
Impact per minute: 1700
Free speed (rpm): 9,000
Bolt capacity (mm): 15

Weight (kg): 1.27
Length (mm): 111.76
Vibration level M/ Sec2: 4.3
Air Consistency (CFM): 8
Recommended hose size (in.): 3/8



VIBROTHERM
by AIRCAT DRIVE

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM