



# 1059-VXL

Compact Impact Wrench

## FEATURE

- Provides 750 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the characteristic aircat unmatched low noise levels.
- The patented grip design provides the operator the ultimate comfort.
- Investment into tooling and materials and a triple injection molding processes enable aircat to produce cosmetic designs that are unmatched in the industry.
- "Three year warranty".

## SPECIFICATIONS

Maximum torque (Nm): 750  
Square drive (in.): 3/8  
Impact per minute: 1700  
Free speed (rpm): 9,000  
Bolt capacity (mm): 15

Weight (kg): 1.27  
Length (mm): 111.76  
Vibration level M/ Sec2: 4.3  
Air Consistency (CFM): 8  
Recommended hose size (in.): 3/8



**VIBROTHERM**  
by **AIRCAT DRIVE**

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM