

AIRCAT

PNEUMATIC TOOLS

1778-VXL

Impact Wrench

FEATURE

- Provides 2300 nm maximum torque.
- Vibrotherm drive® impact wrenches incorporate the completely new aircat design impact wrench mechanism (patent pending).
- The new mechanism reduces vibration levels by between 30%-40% and increases the life of the mechanism by 50%.
- The latest patented aircat muffler system produces the.
- Characteristic aircat unmatched low noise levels.
- The patented grip design provide the customary aircat operator comfort.
- Investment into tooling and materials and a triple injection.
- Molding processes enables aircat to produce cosmetic designs that are unmatched in the industry.
- "three year warranty"

SPECIFICATIONS

Maximum torque (Nm): 1290
Square drive (in.): 3/4
Impact per minute: 1400
Free speed (rpm): 7,500
Bolt capacity (mm): 19

Weight (kg): 2.90
Length (mm): 203.20
Vibration level M/ Sec2: 6.5
Air Consistency (CFM): 8
Recommended hose size (in.): 1/4



VIBROTHERM
by AIRCAT DRIVE

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM