

AIRCAT

PNEUMATIC TOOLS

1993-1-VXL

Vibrotherm Impact Wrench

FEATURE

- Provides 3110 nm of maximum torque.
- Vibrotherm drive® impact wrenches incorporates the new patented aircat design impact wrench mechanism.
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%.
- 6,000 rpm free speed.
- Unmatched power-to-weight ratio.
- Rubber handle grip and rubberized trigger inserts for ultimate comfort.
- Combined friction-ring and through-hole socket retainer.
- Materials, and the triple injection molding processes enables aircat to produce cosmetic designs that are unmatched in the industry.

SPECIFICATIONS

Maximum torque (Nm): 3120

Weight (kg): 8.38

Square drive (in.): 1X2

Length (mm): 340.36

Impact per minute: 950

Vibration level M/ Sec2: 12.7

Free speed (rpm): 6000

Air Consistency (CFM): 10

Bolt capacity (mm): 32

Recommended hose size (in.): 1/2



VIBROTHERM
by AIRCAT DRIVE

Performance Proven Products

+44 1494 883300

AIRCAT-TOOLS.COM

UNIT 8, LANE END INDUSTRIAL PARK, HIGH WYCOMBE, HP14 3BY, UNITED KINGDOM